



AUTOMATIC FLAP DOOR FOR SHAFTS

When closed, the flap door is a reception floor on which the operator safely can deposit, unhook and remove the load without great effort.



Z.A.
67, rue des Vignes
45240 MARCILLY EN
VILLETTE
Tél.: (+33) 02 38 76 12 00
Fax: (+33) 02 38 76 17 25



When opened, the flap door allows the tackle and the load to move up or down.

The movement of the flap door on the floor is protected by grid panels 50x25x4 mm, height 2200 mm on three sides of the shaft.
Power supply: 230 V or 400 V - 50 Hz.



A revolving light turns at every movement of the flap door. The flap door is pre-assembled and tested in our factory-hall.

Resistance:
2000 kg (load
equally
dispatched).



Simple and robust construction:
no special maintenance required.

The operator hoists the load above the access level and pushes the button in order to close the flap door. Once the flap door closed, he can deposit and unhook the charges. In order to open the flap door, the operator re-pushes the button and puts in gear the movement of the flap door.

TRIAX - Z.A. - 67, rue des Vignes - 45240 MARCILLY EN VILLETTE - FRANCE
Tél. (+33) 02 38 76 12 00 - Fax (+33) 02 38 76 17 25
triax@triax-securite.com www.triax-securite.com



LA MANUTENTION SÉCURISÉE

TRIA X

AUTOMATIC FLAP DOOR FOR SHAFTS

Z.A.
67, rue des Vignes
45240 MARCILLY EN
VILLETTE
Tél.: (+33) 02 38 76 12 00
Fax: (+33) 02 38 76 17 25

